



TimberTech2 Silver Plus Underlay

Top quality acoustic underlay with 3mm thick natural rubber

- All the stability you need**
 The high density, fleece-backed natural rubber is extremely stable and prevents movement in your flooring, reducing wear and tear.
- Shhh! Underlay at work**
 This is an underlay with real acoustic performance thanks to its thick materials, cutting down noise levels to make any room more comfortable.
- Dry as a bone**
 Don't worry about moisture rising up from the sub-floor - the silver vapour barrier film protects your floor covering against damp.

Heavy Traffic

Wood



Best for

Cushioning	Moisture Protection	Sound Reduction
Level Floors	Compression Recovery	Underfloor Heating
Hard Wearing	Heat Insulation	Commercial Use*

*Suitable for hotels and public buildings

Technical Data			
Properties	Unit	Value	Method
Density	kg/m ³	950 ± 50	internal
Weight per square metre	kg/m ²	2.8 ± 0.28	internal
Impact Sound Reduction	dB	≥ 21	BS EN ISO 717-2
Thermal Resistance	Tog	0.37	BS 4745:2005
Maximum Compression Load	kN/m ²	2-5	DIN EN 1606
Flammability	Pass		Hot Metal Nut Test
	Low radius of effect		

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive
 Liverpool, L24 8RL
 Tel: 0151 495 3434
 Fax: 0151 420 9062
 Email: sales@qaflooringsolutions.com
 www.qaflooringsolutions.com

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

Simply Better

Available in

Code	QAU-TTS-02
Size	1m x 10m (10m ²)
Thickness	3mm