



TimberTech Neo Acoustic

Underlay

Heavyweight
natural crumb
rubber
underlay with
**outstanding
noise reduction.**

- **Shhh! Underlay at work**
TimberTech Neo Acoustic is a 5mm thick rubber crumb underlay making it a winner for heavy eight jobs. In addition, this superb underlay has a felt backing which provides stability when cutting and installing and an even more impressive 26dB sound reduction.
- **Dry as a bone**
The gold vapour barrier on TimberTech Neo Acoustic prevents moisture rising from the sub-floor – protecting your floor covering against damp.
- **Old tyre, new life**
The high density and compressive strength fully support the floor and prevent movement, keeping it in good shape for a longer life.

Technical Data

Properties	Unit	Value	Method
Thickness	mm	5	internal
Density	kg/m ³	400 ± 50	internal
Weight per square metre	kg/m ²	2.5 ± 10%	internal
Impact Sound Reduction	dB	≥ 26	BS EN ISO 717-2:2013 BS EN ISO 10140-3:2010
Thermal Resistance	Tog	0.73	BS4745:2005
Flammability (hot metal nut test)	Pass - low radius of effect*	BS 4790:1987 (2009)	

*Values derived from similar products

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive

Liverpool, L24 8RL

Tel: 0151 495 3434

Email: sales@qaflooringsolutions.com

www.qaflooringsolutions.com

Simply Better

Heavy
Traffic

Wood



Best for

Cushioning

Moisture
Protection

Sound
Reduction

Level
Floors

Compression
Recovery

Underfloor
Heating

Hard
Wearing

Heat
Insulation

Commercial
Use

Available in

Code QAU-TNA-01

Size 1m x 8m (8m²)

Thickness 5mm