



CombiFelt Acoustic Underlay

Extra-tough felt and rubber combination perfect for **prestige carpets**

■ A touch more luxurious

Giving a firm but truly plush feel under your feet, this is an ideal choice for luxury settings and is widely used under Axminster and quality twist carpets.

■ Built to last

This is an underlay designed for fantastic durability. It won't crumble over time and takes even the heaviest use in its stride - it actually exceeds BS5808 (Heavy Contract Use)!

■ Shhh! Underlay at work

CombiFelt Acoustic has unbelievable impact sound insulation ...so not only does it make your carpet feel softer and more luxurious, you'll notice a real difference in noise levels.

Technical Data

Properties	Value
Quality	Combifelt
Composition	Jute, Wool and Synthetic fibres with a crumb rubber backing
Nominal Weight	72oz/sq. yard 2440g/sq mtr(+/-10%)
Nominal Thickness	10mm (+/-5%)
Roll Dimensions	7.3m x 1.37m
Static Loading BS4939	Thickness Loss - 20% Retained - 80%
Dynamic Loading BS4052	Thickness Loss - 14.5% Retained - 85.5%
Tensile Strength BS2576 & BS5808	Breaking Strength 170N Elongation at 40N 3.7%
Flammability BS4790 Hot Nut	Pass - low radius
Classification	Heavy domestic/heavy contract as per BS5808

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.


QA Flooring Solutions Ltd

Block H, Pickerings Road,
Widnes, Cheshire WA8 8XW
Tel: 0151 495 3434
Fax: 0151 420 9062
Email: sales@qaflooringsolutions.com
www.qaflooringsolutions.com

Simply Better

Heavy
Traffic

Carpet



Best for

Cushioning

Moisture
Protection

Sound
Reduction

Level
Floors

Compression
Recovery

Underfloor
Heating

Hard
Wearing

Heat
Insulation

Commercial
Use*

*Suitable for hotels and public buildings

Available in

Code QAU-CFA-01

Size 1.37m x 7.3m (10m²)

Thickness 10mm