# GA FineFloor FibreBoard

Insulating panels of natural wood fibre, designed to eliminate uneven floors

**Technical Data** 

### On the level

As well as insulation, FibreBoard provides a level subfloor for the final floor covering, offering stable support and helping your floor last longer by smoothing out the most uneven areas.

## Keep out the cold

The exceptional thermal insulation of FibreBoard is perfect for use on very cold subfloors such as cellars, to make your room feel so much cosier and comfortable.

### Easy to fit

Made from traditional natural wood fibre, you'll find FibreBoard really easy to line up, cut and fit - saving you a great deal of time and effort wherever you're installing it.

Properties	4mm (Thin)	5mm (Classic)	7mm (Levelling)
Dimensions [mm]	590 x 850	590 x 850	590 x 856
Qty pcs by pack	22	20	17
Qty m² in a pack	11.03m <sup>2</sup>	10.03m <sup>2</sup>	8.59m <sup>2</sup>
Qty pack on pallet	24	22	18
Qty m² in a pallet	264.8m <sup>2</sup>	220.6m <sup>2</sup>	154.5m <sup>2</sup>
Acoustic Installation	18dB	18dB	18dB
Thermal Conductivity	0.050W/mK	0.050W/mK	0.050W/mK
Compressive Strength	>150 kPa	>150 kPa	>150 kPa
Static Bending Strength	min. 1.6 Mpa	min. 1.6 Mpa	min. 1.6 Mpa
Density	260kg/m <sup>3</sup> <u>+</u> 10%	260kg/m <sup>3</sup> <u>+</u> 10%	260kg/m <sup>3</sup> <u>+</u> 10%
Humidity	up to 9%	up to 9%	up to 9%
Swelling in thickness after 2hours	up to 8%	up to 8%	up to 8%
Levels base irregularity Fine Floor 4mm	up to 2mm	up to 2mm	up to 2mm
Levels base irregularity Fine Floor 5.5mm	up to 3mm	up to 3mm	up to 3mm
Levels base irregularity for Fine Floor 7mm	up to 4mm	up to 4mm	up to 4mm

#### **QA Flooring Solutions Ltd**

Unit 2 Hurricane Drive Liverpool L24 8RL Tel: 0151 495 3434 Fax: 0151 427 0484 Email: sales@gaflooringsolutions.com www.gaflooringsolutions.com

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.



The mark of


responsible forestry

FSC\* C132556

Look for FSC Simply Better certified products.

Medium Traffic

Wood



### **Best for** Moisture Sound Level Underfloor Floors Recoverv Heating Heat Wearing Insulation Uso\* \*Suitable for hotels and public buildings

#### Available in

Code	QAU-FFF-01
Size	590mm x 850m (11.03m <sup>2</sup> )
Thickness	4mm
Code	QAU-FFF-02
Size	590mm x 850m (10.03m <sup>2</sup> )
Thickness	5mm
Code	QAU-FEE-03
	GROTIT 05
Size	590mm x 850m (7.02m <sup>2</sup> )
	590mm x 850m (7.02m <sup>2</sup> )
Size	590mm x 850m (7.02m <sup>2</sup> )
Size Thickness	590mm x 850m (7.02m <sup>2</sup> ) 5mm
Size Thickness Code	590mm x 850m (7.02m <sup>2</sup> ) 5mm QAU-FFF-04 590mm x 856m (8.59m <sup>2</sup> )