



TimberTech Neo

Underlay

Heavyweight
crumb rubber
underlay with
**outstanding
noise
reduction.**

- **Shhh! Underlay at work**
TimberTech Neo gives high insulation against impact sound – really bringing down noise levels and making the room a better place to be.
- **Dry as a bone**
Silver vapour barrier film prevents moisture rising from the sub-floor – protecting your floor covering against damp.
- **Old tyre, new life**
TimberTech Neo is made with rubber from recycled car tyres, which means old tyres don't go into landfill – so it's better for the planet.

Technical Data

Properties	Unit	Value	Method
Density	kg/m ³	400 ± 50	internal
Weight per square metre	kg/m ²	1.2 ± 10%	internal
Impact Sound Reduction	dB	≥ 23	BS EN ISO 717-2:2013 BS EN ISO 10140-3:2010
Thermal Resistance	Tog	0.72	BS4745:2005
Flammability (hot metal nut test)	Pass - low radius of effect*	BS 4790:1987 (2009)	

*Values derived from similar products

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive
Liverpool L24 8RL
Tel: 0151 495 3434
Fax: 0151 427 0484
Email: sales@qaflooringsolutions.com
www.qaflooringsolutions.com

Simply Better

Heavy
Traffic

Wood



Best for

Cushioning

Moisture
Protection

Sound
Reduction

Hard
Wearing

Compression
Recovery

Underfloor
Heating

Hard
Wearing

Heat
Insulation

Commercial
Use

Available in

Code QAU-TNE-01

Size 1m x 10m (10m²)

Thickness 3mm