



TimberTech2 Gold

Underlay

Premium
ultra thick
natural
rubber
underlay
with vapour
barrier

- Stability you can rely on**
 TimberTech2 Gold's heavy mass stability is exceptional, preventing movement in your flooring to keep it looking good longer.
- Quiet please...**
 With its ultra-thick laminated materials TimberTech Gold has outstanding acoustic performance to make any room more comfortable.
- Protects against damp**
 Gold vapour barrier gives superior protection against moisture rising up from the sub-floor - so your room stays dry.

Technical Data

| Properties | Unit | Value | Method |
|---------------------------------------|-------------------|----------------------|-------------------------------|
| Density | kg/m ³ | 950 ± 50 | internal |
| Weight per square metre | kg/m ² | 3.1 ± 0.31 | internal |
| Impact Sound Reduction | dB | ≥ 23 | BS EN ISO 717-2 |
| Thermal Conductivity measured at 10°C | W/m k | 0.036 | DIN 4108 |
| Thermal Resistance | Tog | 0.53 | BS4745:2005 (ISO 5085-1:1989) |
| Maximum Compression Load | kN/m ² | 2-5 | DIN EN 1606 |
| Flammability | Pass | Low radius of effect | Hot Metal Nut Test |

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive

Liverpool L24 8RL

Tel: 0151 495 3434

Fax: 0151 427 0484

Email: sales@qaflooringsolutions.com

www.qaflooringsolutions.com

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

Simply Better

Heavy
Traffic

Wood



Best for

Cushioning

Moisture
Protection

Sound
Reduction

Level
Floors

Compression
Recovery

Underfloor
Heating

Hard
Wearing

Heat
Insulation

Commercial
Use*

*Suitable for hotels and public buildings

Available in

Code QAU-TTG-01

Size 1m x 10m (10m²)

Thickness 3.3mm