GA E-Board Concrete Professional Systems

Underlay system for concrete subfloors with brilliant acoustic performance

Shhh...underlay at work

Truly exceptional impact sound insulation (57dB) and airborne sound insulation (47dB) comes from a two-layer underlay with Acoustic Barrier backed by 6mm Class O Acoustic Foam.

Fire safe and sound

Meeting BS476: parts 6 & 7 - the highest level for Class O - the Acoustic Foam is a fully tested for fire resistance - and peace of mind.

Commercial or residential

Ideal for new, retrofit or renovation projects in offices, homes and hotels, E-Board Concrete fully meets Doc E (July 2003) of the Building Regulations.



Best for



*Suitable for hotels and public buildings

Technical Data				
Properties	Unit	Value	Method	
Airborne Sound Reduction	dB	47	BSEN ISO-140-8	
Impact Sound Reduction	dB	57	BSEN ISO-140-8	

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

QA Flooring Solutions Ltd binding in customers Block H. Pickerings Road

Block H, Pickerings Road, Widnes, Cheshire WA8 8XW Tel: 0151 495 3434 Fax: 0151 420 9062 Email: sales@qaflooringsolutions.com www.gaflooringsolutions.com

_

Code	QAU-EBC-01		
Size	1.2m x 1m (1.2m ²)		
Thickness	9mm		

Available in

Simply Better